

# Rainbow Exterior Primer (WT)

Rainbow Exterior Primer is a water-based wall coating suitable for application on exteriors as an undercoat to exterior emulsions.




## PRODUCT BENEFITS

1. Excellent opacity and whiteness
2. Improves appearance of top coat
3. Does not chalk and can be applied on adequately cured fresh plaster
4. Does not require curing with water
5. Provides excellent adhesion to top coat emulsions
6. Prevents peeling off of top coat emulsions



## PRODUCT FEATURES

### AVAILABLE PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.


### COVERAGE



### DRYING TIME TO TOUCH



### RECOMMENDED USAGE



Can be used for priming plastered walls, asbestos, brick work, concrete, etc  
\*\*Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.

## HOW TO APPLY

### PRE PAINTING STEPS



**PLASTER** New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



**CLEANING** Surface should be free from any loose paint, dust or grease. Growths of fungus, algae or moss should be removed by wire brushing and water. In case of areas having excessive dampness use Appropriate product to limit further dampness.



**FILLING FOR CRACKS** For filling cracks upto 3mm use crack sealant



**FILLING FOR HOLES & DENTS** In case of dents and holes use Rainbow Acrylic Wall Putty or white cement and fine sand in the ratio 1:3

### APPLICATION PROCESS

Sand the surface with sand paper 180 and wipe clean. Mix Rainbow wall putty with 40%-50% pure water and apply on the wall. Let it dry for 6-8 hours. Mix the exterior primer with equal quantity of water and apply with 15-18 nos. brush/roller no.33 and wait for 4-5 hours. Apply emulsion coat over exterior wall primer.

## ADDITIONAL INFORMATION

### PRECAUTIONS

- > Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- > Do not over-thin or over-extend the brush
- > Stir well and strain before use
- > In coastal areas, it is not recommended to leave the primer without the application of top coats for a long period of time

### POST PAINTING CARE

Apply an emulsion coat over Exterior Wall Primer.

### SAFETY FEATURES

- > Kindly refer to the MSDS for Rainbow Exterior Primer (WT) which gives detailed information on safety measures while handling the paint, which is available on request.
- > Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- > Keep out of reach of children and away from eatables.
- > May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- > Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- > Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation
- > Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand or earth.
- > No added Lead, Mercury or Chromium compounds.